


Item No.	Length
S3680	L=1m±15mm
S3681	L=2m±15mm
S3682	L=3m±15mm



Note: DP TO HDMI real machine detection

1. Signal source resolution UXGA: 3840X2160P
2. Refresh rate: 60HZ
3. The video shows no signal jitter, abnormal display such as smear, ghosting, and lack of color
4. The total length of the two ends of the test extension cable is 1000MM / MAX
5. Temperature resistance: 40-70 degrees Celsius

Version	ECN number	Description	Date	Changer
	<b>TOLERANCE</b> INCHES    M/M		<b>SECOMP</b>	
	.X	.015    .030	Description	
	.XX	.010    .010		
.XXX	.005    .05	STANDARD DP-UHDTV Cable, M/M, black		
<b>DRAWN BY</b>	Peter	Item No.	S3680/S3681/S3682	
<b>CHECK BY</b>	Keven	<b>SCALE</b>	NONE	<b>REV.</b> A
<b>APPD BY</b>		<b>UNIT</b>	MM	
		<b>DATE</b>	2022.9.27	1/1

4	IC model: NX3301B	1	SET
3	Interface information: HDMI, male connector, 19PIN gold plated. Gold-plated appearance, ABS version shell.	1	SET
2	Interface information: DP 20PIN, male connector, 20PIN pin, gold plated. Gold-plated appearance, black rubber core, ABS version shell, with hook, black.	1	SET
1	Wire model: CABLE 32#BC (2C+AL) * 4P + 32# BC * 6C + A OD5.0MM	1	PCS
<b>ITEM</b>	<b>STANDARD SPECIFICATION</b>	<b>Q'TY</b>	<b>UNIT</b>