


Big DP JIEK HDMI interface



Note: DP TO HDMI real machine detection

1. Signal source resolution UXGA: 1920 X 1080P
2. Refresh rate: 60HZ
3. The video shows no signal jitter, abnormal display such as smear, ghosting, and lack of color
4. The total length of the two ends of the test extension cable is 1000MM / MAX
5. Temperature resistance: 40-70 degrees Celsius

4	IC model: PTN3361	1	SET
3	Interface information: HDMI, male connector, 19PIN gold plated. Gold-plated appearance, ABS version shell.	1	SET
2	Interface information: DP 20PIN, male connector, 20PIN pin, gold plated. Gold-plated appearance, black rubber core, ABS version shell, with hook, black.	1	SET
1	Wire model: CABLE 30# BC (2C+AL) * 4P + 30# BC * 6C + A OD5.5MM	1	PCS
ITEM	STANDARD SPECIFICATION	Q'TY	UNIT

Version	ECN number	Description	Date	Changer
	TOLERANCE INCHES M/M			
	.X	.015 .030		
	.XX	.010 .010		
	.XXX	.005 .05	STANDARD DP-UHDTV Cable, M/M, black, 5m	
DRAWN BY	Peter	Item No.	S3683	
CHECK BY	Keven	SCALE	NONE	REV. A
		UNIT	MM	
APPD BY		DATE	2022.9.27	
				1/1