



NOTE:

1. Electrical test:
 - (1). 100% open short & miss wire test
 - (2). Insulation resistance: DC 300V 0.01s 10M ohm min.
 - (3). Contact resistance: 3 ohm max.
2. Computer + Monitor test
 - (1). Resolution: 3840*2160@60Hz
3. Marking: Display Port Cable AWM STYLE 20276 80°C 30V VW-1
4. RoHS and REACH Compliant

MATERIAL LIST:

NO.	PARTS NAME	SPECIFICATION DESCRIPTION	Q'ty	REMARK
⑥	Dust Cap	LD PE	2	
⑤	TUBE END	BLACK PVC 45P	2	
④	INNER COVER	LD PE	2	
③	OUTER COVER	DP 20PIN MALE BLACK ABS ASSEMBLY TYPE	2	
②	CONNECTOR	DP 20P/M WITH LATCHING SOLDER TYPE, BLACK INSULATION, THE PIN GOLD PLATED THE SHELL FOR Gold PLATED	2	
①	CABEL	[(30AWG CCS)*1P+D+FAM]*5+(30AWG CCS)+HDPE*4C+AD PVC/BLACK JACKET, OD: 5.5±0.2MM	1	

Item No.	Length
S3685	1000 ± 20 mm
S3686	2000 ± 30 mm
S3687	3000 ± 50 mm

Desc. STANDARD DisplayPort 1.2v Cable , 4K@60Hz, M/M, black

BY	CHK	REVISION RECORD MODIFICATIONS	DATE	REV.
		NEW	2022-09-29	A

