



**NOTE:**

1. Electrical test:
  - (1). 100% open short & miss wire test.
  - (2). Insulation resistance: DC 300V 0.01s 10M ohm min.
  - (3). Contact resistance: 5 ohm max.
2. Computer + Monitor test
  - (1). Resolution: 3840\*2160@120Hz
3. Marking: Display Port Cable AWM STYLE 20276 80°C 30V VW-1
4. RoHS and REACH Compliant

**MATERIAL LIST:**

⑥	Dust Cap	LD PE	2	
⑤	TUBE END	BLACK PVC 45P	2	
④	INNER COVER	LD PE	2	
③	OUTER COVER	DP 20PIN MALE BLACK ABS ASSEMBLY TYPE	2	
②	CONNECTOR	DP 20P/M WITH LATCHING SOLDER TYPE, BLACK INSULATION, THE PIN GOLD PLATED THE SHELL FOR Gold PLATED	2	
①	CABEL	[(30AWG CCS)*1P+D+FAM]*5+ (30AWG CCS)+HDPE*4C+AD PVC/BLACK JACKET, OD: 5.5±0.2MM	1	

Item No.	Length
S3695	1000 ± 20 mm
S3696	2000 ± 30 mm
S3697	3000 ± 50 mm

Desc. STANDARD DisplayPort 1.4v Cable, 8K@60Hz, black

NO.	PARTS NAME	SPECIFICATION DESCRIPTION	Q'ty	REMARK
		NEW	2022-09-29	A
BY	CHK	REVISION RECORD MODIFICATIONS	DATE	REV.

