


WIRE ADDRESS



- Electrical Test:
1. 100% TEST OPEN SHORT MIS-WIRE.
 2. CONTACT RESISTANCE: 3Ω MAX.
 3. INSULATION RESISTANCE: 5MΩ MIN.
 4. HI-POT: 300V DC/10MS.
 5. SUPPORT USB 2.0 480Mbps

NUMBER	1	2	4	Quantity	Unit
F	BLACK TPE (85A)				G
E	USB Micro BSP Aluminum shell(Gold)			1	PCS
D	USB AM Aluminum shell(Gold)			1	PCS
C	MICRO USB 5P BM Reversible type (Gold plated)			1	PCS
B	USB AM(White Insulator,Gold Plated)			1	PCS
A	NON-UL 28#*1P+20#*2C +AL,BLACK TPE JACKET + BLACK COTTON BRAID(CONTAIN GOLD RIBBON),OD:4.2mm			1	PCS
PRODUCT SPECIFICATIONS					

D					
C					
B					
VER.A		REVISE			DATE
GOLD USB 2.0 Cable, A - Micro B (reversible), MM, 0.8 m					
Item	11.02.8819				
Draw	<i>Yoko</i>	Date: 2018.11.16			
Approval					
Duty	F16	BOM.NO:			
Sample NO.					

