



**WIRE ADDRESS**

DB 9P MALE P1	P2 DB 9P FEMALE
1	1
2	2
3	3
4	4
5	5
6	6
7	7
8	8
9	9
Shell	Shell

Electrical Test:  
 1. 100% TEST OPEN SHORT MIS-WIRE.  
 2. CONTACT RESISTANCE:3Ω MAX.  
 3. INSULATION RESISTANCE:5MΩ MIN.  
 4. HI-POT:300V DC/10MS.

NUMBER	DESCRIPTION	Quantity	Unit
1	45P PVC BLACK		G
2	Screw:#4-40(Nickel Plated,Black Molding)	2	PCS
3	DB 9P FEMALE(Black Insulator, Nickel Plated,PIN Gold Plated 1U <sup>m</sup> )	1	PCS
4	DB 9P MALE(Black Insulator, Nickel Plated,PIN Gold Plated 1U <sup>m</sup> )+Front rivet nut	1	PCS
5	NON-UL 30AWG*9C(BC)+AL-foil+Drain .OD=5.0mm BLACK PVC JACKET.	1	PCS

Item	Item	Item	Item
D	VER.A	REVISE	DATE
C	B		
B			
Approval	Draw	Date: 2017.05.15	
Duty	F16		

