



NOTES:

1. MATERIALS

1.1 CABLE: 7/0.12BCx1P+7/0.12BCx2C+AM+D(7/0.12BC)
 +B(16/3/0.12ALM)+WHITE PVC JACKET;
 OD=∅4.0 ± 0.15MM.

CABLE PRINTING: USB 2.0 CABLE FULLY RATED 30V 80°C

1.2 P1: USB 2.0 A TYPE MALE: SOLDER TYPE,
 GOLD FLASH CONTACTS, NICKEL PLATED SHEL

1.3 P2: USB 2.0 MIC B TYPE MALE: SOLDER TYPE,
 GOLD FLASH CONTACTS, NICKEL PLATED SHEL

1.4 ALL HOOD: MOLDED WHITE PVC.

2. TESTING: 100% OPEN AND SHORT TEST.

- 2.1 100% OPEN AND SHORT TEST.
- 2.2 CONDUCTOR RESISTANCE: 3 OHMS MAX.
- 2.3 INSULATION RESISTANCE: 10 MEGOHMS MIN.

3. ALL MATERIAL BE REACH COMPLIANT.

PIN OUT



(BRAID+DRAIN) SHELL



LENGTH TOLERANCE: X. ± 0.5 .X ± 0.2 .XX ± 0.1	SCALE: FREE	CUS. NAME: ROTRONIC
ANGLE TOLERANCE: X' ± 3' .X' ± 1'	UNIT: mm	
	VERSION: 00	PAGE: 1/1

SECOMP		ENG: Harbie
PRODUCT NO: 11.99.8751	CUSTOMER NO:	CHECKED:
DRAWING NO: 0770	PRODUCT DESCRIPTION: USB2.0 AM/MIC BM 0.15M	APPROVED:

00	NEW ISSUE	2020-08-03
REV.	MODIFY DESCRIPTION	DATE