



*TC:tinned copper *D:drain *AM:aluminum foil mylar,*A:Aluminum foil *B:braid

MATERIAL LIST:

| ⑦ | Micro B | Power input | 1 | |
|-----|------------|--|-------|--------|
| ⑥ | OUTER MOLD | PVC color For BLACK | 1 | |
| ⑤ | Housing | ABS Housing Black | 3 | |
| ④ | PCB | USB Signal amplifier IC | 3 | |
| ③ | USB A TYPE | USB A /F Solder Type, Blue PBT Insulation, The Pin Gold Plating, the shell for Nickel Plating with PCB | 1 | |
| ② | USB TYPE C | USB TYPE C /M, Black PBT Insulation, The Pin Gold Plating, the shell for Nickel Plating | 1 | |
| ① | CABLE | USB 3.0 (28AWG TC*1P+D+AM)*2+(28AWG TC*1P)+(24AWG TC*2C)+A+D+B(AL-MG) OD:5.5±0.2mm | 1 | |
| NO. | PARTS NAME | SPECIFICATION STANDARD | QT' Y | REMARK |

NOTE:

1. Electrical test:
 - (1). 100% computer+ SSD test
 2. Data Transfer: Up to 5Gbps
 3. Output voltages :5V DC.
 4. Output current:900mA.
- Operation temperature:-10°C ~+60°C
 Storage temperature:-20°C ~ +80°C
 RoHS 2.0 and REACH Compliant

| 12.04.1068 | 20000±200 | ROLINE Ultra Long USB3.2 Gen1 Extension Cable, C-A, M/F, 20m |
|------------|-------------|--|
| ITEM NO. | Length (mm) | DESC. |

| | | NEW | 2023-03-30 | A |
|----|-----|-------------------------------|------------|------|
| BY | CHK | REVISION RECORD MODIFICATIONS | DATE | REV. |

SECOMP