

1

2





3

4



5

6

Total length (optional)



roline U/UTP PATCH CABLE 24AWG 4PR ETL Verified rated ANSI/TIA 568C.2 CAT.6 XXXXXX-X



- (1) Jacket Color : Red(RAL3031)
- (2) Wiring:T568B

item no.	length	tolerance
21.15.1511	0.3M	+20 -0
21.15.1521	0.5M	+20 -0
21.15.1531	1M	+20 -0
21.15.0924	1.5M	+20 -0
21.15.1541	2M	+20 -10
21.15.1551	3M	+20 -10
21.15.1561	5M	+30 -20
21.15.1571	7M	+30 -20
21.15.1581	10M	+30 -20
21.15.1591	15M	+30 -20
21.15.1601	20M	+70 -30

Specification :

- Material :
- RJ45 Plug :
 - Housing : Polycarbonate, Transparent color.
 - Contact material : Phosphor Bronze with 50-60 micro-inch Nickel plated.
 - Contact finished : Min. 50 micro-inch Gold plated.
 - Molding: PVC.
 - Cable :
 - Jacket : PVC.
 - Conductor : 24 AWG stranded copper.
 - Isolation : PE.
 - Isolation Cross Bar for 4 pairs : PE.
 - Cable structure : U/UTP, 4 twisted pair with Cross Bar.
 - Minimum Bending Radius: 50mm

item no	21.15.1511	21.15.1521	21.15.1531	21.15.0924	21.15.1541
	21.15.1551	21.15.1561	21.15.1571	21.15.1581	21.15.1591
Desc	ROLINE Cat 6 U/UTP Patch Cord,Red				
"#": Matching DIM.	DRAWING	23.JuL.2016	byz		
"*": Important DIM.	CHECK	23.JuL.2016	Jane		
Others General DIM.	APPROVAL	23.JuL.2016	Jaimy		
GENERAL TOLERANCE OF DIMENSIONS		DATE	NAME		
X.XXX ±0.005 X.XX ±0.05 X.X ±0.1	SCALE	1/1 (A4)	UNIT	mm	
	DRAWING NO.				
	DRAWING CLASSIFICATION		S	SHEET	1 OF 1

No.	MODIFIED AREA	ORIGINAL	MODIFY	DATE	MODIFIER

1

2

0

3

4

10cm

5

6

