



Specification:

1. LC(Short boot) Connector :

Mode	Ferrule	Housing	Clip	Boot	Tube	Cap
MM	Zirconia(ø1.25mm)	Ivory(PC)	Ivory(PP)	White(TPE)	White/Yellow(PVC)	White(PE)

2. Cable Type : Zipcord

Category	Jacket O.D.	Jacket Material	Color
OM4(50/125um)	ø2.0mm	PVC	Violet

3. Shrink Tube
4. Length : xM

Part No. Table

Part NO.	Description	Length
21.15.8750	OM4 50/125µm, LC-LC	0.5M
21.15.8751	OM4 50/125µm, LC-LC	1M
21.15.8752	OM4 50/125µm, LC-LC	2M
21.15.8753	OM4 50/125µm, LC-LC	3M
21.15.8754	OM4 50/125µm, LC-LC	7M
21.15.8755	OM4 50/125µm, LC-LC	5M
21.15.8756	OM4 50/125µm, LC-LC	15M
21.15.8757	OM4 50/125µm, LC-LC	20M
21.15.8758	OM4 50/125µm, LC-LC	10M

Performance:

- a. Insertion Loss : Multimode<0.3 dB
- b. Fiber Extention : -0.05um < H < +0.05um
- c. ø1.25mm Ferrule End-face Radius : 7 < R < 25mm
- d. Apex Offset : < 50um
- e. Insertion Loss will be Increased after 500 mating : 0.2 dB Max
- f. Operating Temperature : -20°C to +70°C
- g. Storage Temperature : -40°C to +80°C

"#": Matching DIM. "*": Important DIM. Others General DIM. GENERAL TOLERANCE OF DIMENSIONS X.XXX ±0.005 X.XX ±0.05 X.X ±0.1	DRAWING	12.JUL.2021	YMN	
	CHECK	12.JUL.2021	DAY	
	APPROVAL	12.JUL.2021	FRANK	
		DATE	NAME	ITEM NO.: AS Part No. Table
SCALE	1/1 (A4)	UNIT	mm	DES.: ROLINE Cable FO 50/125µm LC-LC OM4, Violet
		DRAWING NO. ROLINE Cable FO 50/125µm LC-LC OM4, Violet(S02)		
		DRAWING CLASSIFICATION		