



Note:  
 ROHS 2.0 & REACH Compliant  
 2. The out jacket is conform to IEC60332-1, EN60754-2, EN 61034-2  
 3. Min. Bending Radius: Static:12mm, Dynamic:24mm

Test:  
 Grade Designation: Each to Reference

Type	Single-mode
Insertion Loss	≤0.3dB
Return Loss	≥50dB
Test Wavelength	1310nm

**MATERIAL LIST:**

				ITEM NO.	DESC.
⑥	LC Simplex Clip Blue	2pcs		21. 15. 8840	ROLINE FO Jumper Cable OS2, Simplex, OD1.2mm, LC/LC, 0.5m
⑤	LC Dust Cap White	2pcs		21. 15. 8841	ROLINE FO Jumper Cable OS2, Simplex, OD1.2mm, LC/LC, 1m
④	LC Simplex Connector Blue	2pcs		21. 15. 8842	ROLINE FO Jumper Cable OS2, Simplex, OD1.2mm, LC/LC, 2m
③	LC 1.2 white short boot	2pcs		21. 15. 8843	ROLINE FO Jumper Cable OS2, Simplex, OD1.2mm, LC/LC, 3m
②	LC/UPC SM Ceramic Ferrule	2pcs		21. 15. 8845	ROLINE FO Jumper Cable OS2, Simplex, OD1.2mm, LC/LC, 5m
①	Fiber Optical Cable yellow 9/125 G652.D OS2 Simplex Ø1.2mm LSZH	L+100		21. 15. 8846	ROLINE FO Jumper Cable OS2, Simplex, OD1.2mm, LC/LC, 7m
NO.	SPECIFICATION STANDARD	QT' Y	REMARK	21. 15. 8847	ROLINE FO Jumper Cable OS2, Simplex, OD1.2mm, LC/LC, 10m

		Add Min. Bending Radius	2022-1-24	A1
		NEW	2017-11-24	A
BY	CHK	REVISION RECORD MODIFICATIONS	DATE	REV.

