



Note:
 1. ROHS 2.0 Compliant and REACH Compliant
 2. The out jacket is conform to IEC60332-1, EN60754-2, EN61034-2
 3. Min. Bending Radius: Static: 12mm Dynamic: 24mm

Test:
 Grade Designation: Each to Reference

Type	Multi-Mode
Insertion Loss	≤ 0.3dB
Return Loss	≥ 30dB
Test Wavelength	850nm

MATERIAL LIST:

⑧	Ring 1, 2	4pcs	
⑦	Black Heat Shrink Tube	2pcs	
⑥	LC Clip Erika violet	2pcs	
⑤	LC Dust Cap White	4pcs	
④	LC Duplex Connector Erika violet	4pcs	
③	LC 1.2 white short boot	4pcs	
②	LC/UPC MM Ceramic Ferrule	4pcs	
①	Fiber Optical Cable Erika violet (RAL4003) 50/125 OM4 Duplex ϕ 1.2mm LSZH	L+100	
NO.	SPECIFICATION STANDARD	QT' Y	REMARK

ITEM NO.	DESC.
21.15.9261	ROLINE FO Jumper Cable, SLIM, OM4, OD 1.2mm, LC/LC, 1m
21.15.9262	ROLINE FO Jumper Cable, SLIM, OM4, OD 1.2mm, LC/LC, 2m
21.15.9263	ROLINE FO Jumper Cable, SLIM, OM4, OD 1.2mm, LC/LC, 3m
21.15.9264	ROLINE FO Jumper Cable, SLIM, OM4, OD 1.2mm, LC/LC, 5m
21.15.9266	ROLINE FO Jumper Cable, SLIM, OM4, OD 1.2mm, LC/LC, 7m
21.15.9265	ROLINE FO Jumper Cable, SLIM, OM4, OD 1.2mm, LC/LC, 10m

		Add Min. Bending Radius	2022-1-24	A1
		NEW	2017-7-17	A
BY	CHK	REVISION RECORD MODIFICATIONS	DATE	REV.

