



MATERIAL LIST:

| NO. | PARTS NAME | SPECIFICATION DESCRIPTION |
|-----|----------------|---|
| ① | CABLE | UTP [24AWG 7*0.19±0.015mm((Bare Copper)*1PR)]*4+PVC OD:5.8±0.3mm COLOR:GREEN |
| ② | RJ45 CONNECTOR | RJ45,8P8C,TWO FORK GOLD PLATED CONTACTS |
| ③ | MOLDING | MOLDING PVC , COLOR:GREEN |

(1)Jacket Color:Green(RAL 6016)
(2)wiring:T568B

| Item No. | Length(M) | Tolerance (MM) |
|------------|-----------|----------------|
| 21.99.1440 | 0.5 | +20/-10 |
| 21.99.1441 | 1 | +/-20 |
| 21.99.1442 | 2 | +/-40 |
| 21.99.1443 | 3 | +/-60 |
| 21.99.1445 | 5 | +/-110 |
| 21.99.1446 | 7 | +/-140 |
| 21.99.1447 | 10 | +/-200 |
| 21.99.1448 | 15 | +/-310 |
| 21.99.1449 | 20 | +/-400 |

Marking: E213738 CM (UL) C(UL) UTP PATCH CORD 24AWG 4P ISO/IEC 11801 AND TIA/EIA 568 CAT6A

ELECTRONIC TEST:

- A. OPEN/SHORT : 100%.
- B. WORKING TEMPERATURES:-20~60°C
- C. Minimum Banding Radius: 46MM

| | | | | | |
|-------------|------------|------------|-------------------------------------|------------|------------|
| Item No. | 21.99.1440 | 21.99.1441 | 21.99.1442 | 21.99.1443 | 21.99.1445 |
| | 21.99.1446 | 21.99.1447 | 21.99.1448 | 21.99.1449 | |
| REMARK: NO | CHA NO | DESC | VALUE UTP Cat. 6a Patch Cord, green | | |
| DRAWN BY | WEIHAIYAN | | SECOMP | | |
| APPROVED BY | MORGAN | | | | |
| DATE | 2015.09.22 | | | | |