



MATERIAL LIST:

NO.	PARTS NAME	SPECIFICATION DESCRIPTION
①	CABLE	UTP [24AWG 7*0.19±0.015mm((Bare Copper)*1PR)*4+PVC OD:5.8±0.3mm COLOR:BLACK
②	RJ45 CONNECTOR	RJ45,8P8C,TWO FORK GOLD PLATED CONTACTS
③	MOLDING	MOLDING PVC , COLOR:BLACK

(1)Jacket Color:Black(RAL 9011)

(2)wiring:T568B

Item No.	Length (M)	Tolerance(MM)
21.99.1460	0.5	+20/-10
21.99.1461	1	+/-20
21.99.1462	2	+/-40
21.99.1463	3	+/-60
21.99.1465	5	+/-110
21.99.1466	7	+/-140
21.99.1467	10	+/-200
21.99.1468	15	+/-310
21.99.1469	20	+/-400

Marking: E213738 CM (UL) C(UL) UTP PATCH CORD 24AWG 4P ISO/IEC 11801 AND TIA/EIA 568 CAT6A

ELECTRONIC TEST:

- A. OPEN/SHORT : 100%.
- B. WORKING TEMPERATURES:-20~60°C
- C. Minimum Banding Radius: 46MM

Item No.	21.99.1460	21.99.1461	21.99.1462	21.99.1463	21.99.1465
	21.99.1466	21.99.1467	21.99.1468	21.99.1469	
REMARK: NO	CHA NO	DESC	VALUE UTP Cat. 6a Patch Cord, black		
DRAWN BY	WEIHAIYAN		SECOMP		
APPROVED BY	MORGAN				
DATE	2015.09.22				