



Note:

1. ROHS 2.0 & REACH Compliant
2. The out jacket is conform to IEC60332-1, EN60754-2, EN 61034-2
3. Min. Bending Radius: Static: 30mm Dynamic: 60mm

TYPE	MULTI-MODE
Insertion LOSS	≤0.3dB
Return LOSS	≥30dB
Test Wavelength	850nm

⑭	Ring 1 2 Yellow	4pcs	
⑬	ST Connector	2pcs	
⑫	ST Dust Cap	2pcs	
⑪	ST Black Boot	1pcs	
⑩	ST Red Boot	1pcs	
⑨	ST MM Ferrule	2pcs	
⑧	Blcak Heat Shrink Tube	2pcs	
⑦	LC Aqua Duplex Clip	1pcs	
⑥	LC MM Aqua Duplex Connector	2pcs	
⑤	LC Dust Cap White	2pcs	
④	LC White Boot	1pcs	
③	LC White Boot	1pcs	
②	LC MM Ferrule	2pcs	
①	Fiber Optical Cable Duplex ϕ 3.0mm OM3 50/125um Aqua LSZH	L+0.1m	

21.99.8728	VALUE Fibre Optic Jumper Cable, 50/125 μ m, LC-ST, OM3, Aqua, 10m
21.99.8725	VALUE Fibre Optic Jumper Cable, 50/125 μ m, LC-ST, OM3, Aqua, 5m
21.99.8723	VALUE Fibre Optic Jumper Cable, 50/125 μ m, LC-ST, OM3, Aqua, 3m
21.99.8722	VALUE Fibre Optic Jumper Cable, 50/125 μ m, LC-ST, OM3, Aqua, 2m
21.99.8721	VALUE Fibre Optic Jumper Cable, 50/125 μ m, LC-ST, OM3, Aqua, 1m
21.99.8720	VALUE Fibre Optic Jumper Cable, 50/125 μ m, LC-ST, OM3, Aqua, 0.5m

NO.	SPECIFICATION STANDARD	QT' Y	REMARK
	Add Min. Bending Radius	2022-1-24	A1
	NEW	2017-8-30	A
BY	CHK	REVISION RECORD MODIFICATIONS	DATE
			REV.

SECOMP