

ROLINE GOLD USB 3.2 Gen 1 Cable, A - B, M/M, 3 m

| | |
|---------------------------|---------------|
| Product No. | 11.02.8903 |
| Manufacturer | ROLINE |
| Manufacturer No. | 11.02.8903 |
| EAN (single piece) | 7611990195572 |



USB 3.0 / USB 3.2 Gen 1 SuperSpeed cable with high quality and improved shielding.

- The plugs are gold coated to enhance their contact durability
- Nylon-reinforced outer material for a better stability
- Supports data transfer rates of up to 5 Gbit/s
- Connectors: USB 3 Type A M to Type B M

ROLINE GOLD - Top quality without any compromises!

Cables in ROLINE GOLD quality come with high quality shielding and gilded contacts for contact safety even at high plug-in cycles. The plugs are gold coated to enhance their contact durability. Nylon-reinforced outer material in golden/black provides a better stability and gives the cable a stunning look.

Note: According to the current specifications of USB.org we have adapted the technical data of our USB 3 products. The new designation for the already known USB specifications has been changed to USB 3.2 Gen 1 (formerly USB 3.0 / USB 3.1 Gen 1) and USB 3.2 Gen 2 (formerly USB 3.1 / USB 3.1 Gen 2).

Technical specifications

| | |
|---------------|---------------|
| Manufacturer | ROLINE |
| Product group | Cable |
| Product type | USB 3.2 Cable |

| | |
|------------------------------------|--|
| Colour | black / gold |
| Length | 3 m |
| Transfer quality | USB 3.2 Gen 1 SuperSpeed 5 Gbit/s (USB 3.1 Gen 1, USB 3.0) |
| Connection ports | USB 3 Type A Male / USB 3 Type B Male |
| side 1 connector | USB 3.0 Type A Male |
| side 2 connector | USB 3.0 Type B Male |
| Side 1 Connector Type | USB 3 Type A |
| Side 1 Connector Gender | Male |
| Side 2 Connector Type | USB 3 Type B |
| Side 2 Connector Gender | Male |
| Maximum data transfer rate | 5 Gbit/s |
| Area of application | External |
| Cable shielding | Double screened |
| Connector Casing | Gold |
| Hand locking screws | no |
| Weight | 160.8 g |
| Height of packaging (single piece) | 30 mm |
| Width of packaging (single piece) | 150 mm |
| Depth of packaging (single piece) | 200 mm |
| Package weight (single piece) | 0.165 kg |