

ROLINE HDMI High Speed Cable + Ethernet, M/M, black /silver, 7.5 m

| | |
|---------------------------|---------------|
| Product No. | 11.04.5854 |
| Manufacturer | ROLINE |
| Manufacturer No. | 11.04.5854 |
| EAN (single piece) | 7611990144419 |



ROLINE HDMI cable with double-sided HDMI connection for connecting an ultrabook, notebook/laptop or PC to a monitor, TV or projector - for screen transmissions in excellent quality with a resolution of up to 1920 x 1080 @60Hz!

- HDMI is a universal connection standard for the transmission of video and audio signals. Applications include mainly the connection of monitors and televisions to computers, BluRay players and similar devices.
- The connector requires less space and is therefore more suitable for portable display devices (ultrabooks, notebooks/laptops) or for 2 connectors on a graphics card (on a slot plate).
- The rugged nylon braid protects the HDMI cable effectively and makes it look stunning.
- High-quality, double-shielded cable (foil+braid) with gold-plated contacts for optimum transmission of image signals
- Supports 3D video
- HDMI Ethernet channel
- Audio return channel for forwarding signals to the audio/video receiver.
- Black metallic connector housing

Technical specifications

Manufacturer ROLINE

| | |
|------------------------------------|-------------------------------------|
| Product group | HDMI cables |
| Product type | HDMI High Speed Cable with Ethernet |
| Colour | black /silver |
| Length | 7.5 m |
| Transfer quality | HDMI High Speed with Ethernet |
| Max. resolution | 1920 x 1080 @60Hz (2K, Full HD) |
| side 1 connector | HDMI 19 Male |
| side 2 connector | HDMI 19 Male |
| Side 1 Connector Type | HDMI Type A |
| Side 1 Connector Gender | Male |
| Side 2 Connector Type | HDMI Type A |
| Side 2 Connector Gender | Male |
| Area of application | External |
| Cable shielding | Double screened |
| Technical particularity | HDMI High Speed with Ethernet |
| Weight | 471.9 g |
| Height of packaging (single piece) | 30 mm |
| Width of packaging (single piece) | 190 mm |
| Depth of packaging (single piece) | 190 mm |
| Package weight (single piece) | 0.49 kg |