ROLINE USB to RS-422/485 Converter

Product No. 12.02.1174

ROLINE

Manufacturer No. 12.02.1174

EAN (single piece) 7630049634329



Manufacturer





USB-to-serial converter for use with computers without a serial interface and mobile devices, which often only offer USB interfaces.

This converter provides an extra Serial RS-422/485 port via USB connection

- To connect serial devices (e.g. modem) to one USB port
- Built-in +/- 15 KV ESD protection
- DB9 female to 5 pin terminal block adapter included
- Supports data transfer rates of up to 921.6 kbit/s
- Power supply via USB interface from PC / notebook
- Plug & play
- Supports Microsoft Windows and Linux

Technical specifications	
Manufacturer	ROLINE
Product group	Adapters, Terminators, Converters
Product type	USB - Serial Converter
Colour	black
Length	1.2 m
Scope of delivery	Converter Cable, DB9 Female - to 5 Pin Terminal Block Adapter, User Manual
Side 1 connection (PC)	USB A Male

Side 2 connection (Peripherals) DB9 Male (Peripherals) Side 1 Connector Type USB 2.0 Type A Side 1 Connector Gender Male Gender Side 2 Connector Gender D-Sub 9-pin (DE-9) Side 2 Connector Gender Male Gender Conversion direction USB - R5422/485 Colour (Cable) black Area of application External Hand locking screws yes Technical particularity Windows 7 / 8 / 10 / 11 and Linux 2.6.x or later Operating temperature min. 0° C Operating temperature max. -30° C Storage temperature max. 45 ° C Height 15 mm Width 33 mm Depth 45 mm Weight 81 g Height of packaging (single piece) 20 mm Width of packaging (single piece) 100 mm Package weight (single piece) 0.25 kg		
Side 1 Connector Gender Side 2 Connector Type D-Sub 9-pin (DE-9) Side 2 Connector Gender Conversion direction USB - RS422/485 Colour (Cable) black Area of application External Hand locking screws Yes Technical particularity Windows 7 / 8 / 10 / 11 and Linux 2.6.x or later Operating temperature min. Operating temperature min. Storage temperature min. Storage temperature max. Height 15 mm Width 33 mm Depth 45 mm Weight Height of packaging (single piece) Windows 20 mm (single piece) Package weight (single 0.25 kg		DB9 Male
Gender Side 2 Connector Type D-Sub 9-pin (DE-9) Side 2 Connector Male Gender Conversion direction USB - RS422/485 Colour (Cable) black Area of application External Hand locking screws yes Technical particularity Windows 7 / 8 / 10 / 11 and Linux 2.6.x or later Operating temperature min. Operating temperature min. Storage temperature min. Storage temperature max. Height 15 mm Width 33 mm Depth 45 mm Weight 81 g Height of packaging (single piece) Use Mark Storage weight (single Dece) Package weight (single O.25 kg	Side 1 Connector Type	USB 2.0 Type A
Side 2 Connector Gender Conversion direction USB - RS422/485 Colour (Cable) black Area of application External Hand locking screws Yes Technical particularity Windows 7 / 8 / 10 / 11 and Linux 2.6.x or later Operating temperature min. Operating temperature min. Operating temperature min. Storage temperature min. 45 °C max. Height 15 mm Width 33 mm Depth 45 mm Weight 81 g Height of packaging (single piece) Width of packaging (single piece) Depth of packaging (single piece) Package weight (single 0.25 kg		Male
Gender Conversion direction USB - R5422/485 Colour (Cable) black Area of application External Hand locking screws Yes Technical particularity Windows 7 / 8 / 10 / 11 and Linux 2.6.x or later Operating temperature min. Operating temperature max. Storage temperature min. Storage temperature min. Storage temperature max. Height 15 mm Width 33 mm Depth 45 mm Weight 81 g Height of packaging (single piece) Width of packaging (single piece) Package weight (single Package weight (singl	Side 2 Connector Type	D-Sub 9-pin (DE-9)
Colour (Cable) black Area of application External Hand locking screws yes Technical particularity Windows 7 / 8 / 10 / 11 and Linux 2.6.x or later Operating temperature min. Operating temperature max. Storage temperature min. Storage temperature max. Height 15 mm Width 33 mm Depth 45 mm Weight 81 g Height of packaging (single piece) Package weight (single 0.25 kg		Male
Area of application External Hand locking screws yes Technical particularity Windows 7 / 8 / 10 / 11 and Linux 2.6.x or later Operating temperature min. Operating temperature max. Storage temperature min. Storage temperature max. Height 15 mm Width 33 mm Depth 45 mm Weight 81 g Height of packaging (single piece) Width of packaging (single piece) Package weight (single of packaging (single piece)	Conversion direction	USB - RS422/485
Hand locking screws yes Technical particularity Windows 7 / 8 / 10 / 11 and Linux 2.6.x or later Operating temperature min. Operating temperature max. Storage temperature min. Storage temperature	Colour (Cable)	black
Technical particularity Windows 7 / 8 / 10 / 11 and Linux 2.6.x or later Operating temperature min. Operating temperature foo °C max. Storage temperature min. Storage temperature max. Height 15 mm Width 33 mm Depth 45 mm Weight 81 g Height of packaging (single piece) Width of packaging (single piece) Depth of packaging (single piece) Package weight (single 0.25 kg	Area of application	External
Operating temperature min. Operating temperature min. Operating temperature max. Storage temperature min. Storage temperature min. Storage temperature max. Height 15 mm Width 33 mm Depth 45 mm Weight 81 g Height of packaging (single piece) Width of packaging (single piece) Depth of packaging (single piece) Package weight (single 0.25 kg	Hand locking screws	yes
min. Operating temperature max. Storage temperature and an	Technical particularity	Windows 7 / 8 / 10 / 11 and Linux 2.6.x or later
max. Storage temperature min. Storage temperature 85 °C max. Height 15 mm Width 33 mm Depth 45 mm Weight 81 g Height of packaging (single piece) Width of packaging (single piece) Depth of packaging (single piece) Package weight (single 0.25 kg		0 °C
min. Storage temperature max. Height 15 mm Width 33 mm Depth 45 mm Weight 81 g Height of packaging (single piece) Width of packaging (single piece) Depth of packaging (single piece) Package weight (single) 0.25 kg		60 °C
max. Height 15 mm Width 33 mm Depth 45 mm Weight 81 g Height of packaging 20 mm (single piece) Width of packaging (single piece) Depth of packaging 200 mm (single piece) Package weight (single 0.25 kg		-30 °C
Width 33 mm Depth 45 mm Weight 81 g Height of packaging (single piece) Width of packaging 100 mm (single piece) Depth of packaging 200 mm (single piece) Package weight (single 0.25 kg		85 °C
Depth 45 mm Weight 81 g Height of packaging 20 mm (single piece) Width of packaging 100 mm (single piece) Depth of packaging 200 mm (single piece) Package weight (single 0.25 kg	Height	15 mm
Weight 81 g Height of packaging (single piece) Width of packaging (single piece) Depth of packaging (single piece) Package weight (single 0.25 kg	Width	33 mm
Height of packaging (single piece) Width of packaging (single piece) Depth of packaging (single piece) Package weight (single 0.25 kg	Depth	45 mm
(single piece) Width of packaging 100 mm (single piece) Depth of packaging 200 mm (single piece) Package weight (single 0.25 kg	Weight	81 g
(single piece) Depth of packaging 200 mm (single piece) Package weight (single 0.25 kg		20 mm
(single piece) Package weight (single 0.25 kg		100 mm
		200 mm
		0.25 kg