ROLINE S/FTP (PiMF) Patch Cord, Cat.6 (Class E), grey, 2 m

Product No. 21.15.0832

Designed for Profession

Manufacturer

ROLINE


Manufacturer No.

21.15.0832

EAN (single piece)

7611990155743











Patch cable for networking connections between devices. Prepared double shielded Twisted Pair cable with screened RJ-45 connectors on both ends. Durable due to moulded kink protection. Flexible cable, suitable for narrow bending. High quality plugs with gold plated contacts. Contact settings 1:1, in accordance with the EIA/TIA 568 standard. Construction: 4-pair stranded copper wire. Complete braid shielding. Pairs shielded with aluminium clad polyester foil.

For a structured cabling system we recommend to use the following components: ROLINE Cat.6 S/FTP Cable, Solid Wire, AWG23: 21.15.0890 (100 m), 21.15.0891 (300 m); ROLINE Cat.6 Flush Mount Wall Jack, shielded: 25.16.8492 (white), 25.16.8493 (ivory); ROLINE Cat.6 Surface Mount Wall Jack, shielded: 25.16.8392 (white), 25.16.8393 (ivory); ROLINE Cat.6 19" Patch Panel, 24 Ports, shielded: 26.11.0351 (light grey), 26.11.0361 (black); ROLINE Cat.6 S/FTP Patch Cord, grey, 5 m: 21.15.0835. The accredited German laboratory GHMT has tested and certified this product combination, in a Channel of 100 meters, as being compliant to Class E specifications; certificate no. z2365b-10-E (with flush mount)/z2364b-10-E (with surface mount).

	ications

Manufacturer

ROLINE

Product group	Twisted Pair Cable	
Product type	S/FTP Patchcord	
Colour	grey	
Length	2 m	
Shield type	SFTP	
Transfer quality	Cat6 / Class E	
Impedance	100 Ohm	
Quantity of wires	8	
Conductor type	Wire	
Crossed	no	
Locking lever	no	
Anti-kink sleeve	Moulded-on	
Colour (Spout)	grey	
Cable LSOH	no	
Side 1 Connector Type	RJ-45	
Side 1 Connector Gender	Male	
Side 2 Connector Type	RJ-45	
Side 2 Connector Gender	Male	
Connector Type RJ45	Standard	
Weight	84.9 g	
Height of packaging (single piece)	20 mm	
Width of packaging (single piece)	160 mm	
Depth of packaging (single piece)	220 mm	
Package weight (single piece)	0.09 kg	