

# ROLINE UTP Data Center Patch Cord Cat.6A (Class EA), LSOH, Slim, white, 1.5 m

**Product No.** 21.15.0984  
**Manufacturer** ROLINE  
**Manufacturer No.** 21.15.0984  
**EAN (single piece)** 7630049610620



**Category 6A twisted-pair patch cable with RJ-45 connectors on both sides. Particularly thin and flexible cable with individual pairs of wires for use in confined spaces, such as in data centres.**

- Durable thanks to moulded-on kink protection
- Suitable as patch cable in patch panels or as device connection cable and intended for use in the LAN
- Contact assignment: 1:1 according to EIA/TIA568, 8 cores
- Structure: 8 cores stranded wire

## Technical specifications

Manufacturer	ROLINE
Product group	Twisted Pair Cable
Product type	UTP Patch Cables
Colour	white
Length	1.5 m
Shield type	UTP

Transfer quality	Cat6A / Class EA
------------------	------------------

Quantity of wires	8
-------------------	---

Conductor type	Wire
----------------	------

Crossed	no
---------	----

Slim cable	yes
------------	-----

Locking lever	yes
---------------	-----

Anti-kink sleeve	Moulded-on
------------------	------------

External cable diameter	3.4 +/- 0.2mm
-------------------------	---------------

Cable LSOH	yes
------------	-----

Side 1 Connector Type	RJ-45
-----------------------	-------

Side 1 Connector Gender	Male
-------------------------	------

Side 2 Connector Type	RJ-45
-----------------------	-------

Side 2 Connector Gender	Male
-------------------------	------

Connector Type RJ45	Standard
---------------------	----------

Operating temperature min.	-10 °C
----------------------------	--------

Operating temperature max.	60 °C
----------------------------	-------

Weight	25.5 g
--------	--------

Height of packaging (single piece)	10 mm
------------------------------------	-------

Width of packaging (single piece)	120 mm
-----------------------------------	--------

Depth of packaging (single piece)	150 mm
-----------------------------------	--------

Package weight (single piece)	0.027 kg
-------------------------------	----------