

# ROLINE S/FTP (PiMF) Patch Cord, Cat.6 (Class E), orange, 0.5 m

|                           |               |
|---------------------------|---------------|
| <b>Product No.</b>        | 21.15.1327    |
| <b>Manufacturer</b>       | ROLINE        |
| <b>Manufacturer No.</b>   | 21.15.1327    |
| <b>EAN (single piece)</b> | 7611990124022 |



Patch cable for networking connections between devices. Prepared double shielded Twisted Pair cable with screened RJ-45 connectors on both ends. Durable due to moulded kink protection. Flexible cable, suitable for narrow bending. High quality plugs with gold plated contacts. Contact settings 1:1, in accordance with the EIA/TIA 568 standard. Construction: 4-pair stranded copper wire. Complete braid shielding. Pairs shielded with aluminium clad polyester foil.

For a structured cabling system we recommend to use the following components: ROLINE Cat.6 S/FTP Cable, Solid Wire, AWG23: 21.15.0890 (100 m), 21.15.0891 (300 m); ROLINE Cat.6 Flush Mount Wall Jack, shielded: 25.16.8492 (white), 25.16.8493 (ivory); ROLINE Cat.6 Surface Mount Wall Jack, shielded: 25.16.8392 (white), 25.16.8393 (ivory); ROLINE Cat.6 19" Patch Panel, 24 Ports, shielded: 26.11.0351 (light grey), 26.11.0361 (black); ROLINE Cat.6 S/FTP Patch Cord, grey, 5 m: 21.15.0835. The accredited German laboratory GHMT has tested and certified this product combination, in a Channel of 100 meters, as being compliant to Class E specifications; certificate no. z2365b-10-E (with flush mount)/z2364b-10-E (with surface mount).

## Technical specifications

|              |        |
|--------------|--------|
| Manufacturer | ROLINE |
|--------------|--------|

|                                    |                    |
|------------------------------------|--------------------|
| Product group                      | Twisted Pair Cable |
| Product type                       | S/FTP Patchcord    |
| Colour                             | orange             |
| Length                             | 0.5 m              |
| Shield type                        | SFTP               |
| Transfer quality                   | Cat6 / Class E     |
| Impedance                          | 100 Ohm            |
| Quantity of wires                  | 8                  |
| Conductor type                     | Wire               |
| Crossed                            | no                 |
| Locking lever                      | no                 |
| Anti-kink sleeve                   | Moulded-on         |
| Colour (Spout)                     | orange             |
| Cable LSOH                         | no                 |
| Side 1 Connector Type              | RJ-45              |
| Side 1 Connector Gender            | Male               |
| Side 2 Connector Type              | RJ-45              |
| Side 2 Connector Gender            | Male               |
| Connector Type RJ45                | Standard           |
| Weight                             | 29.1 g             |
| Height of packaging (single piece) | 10 mm              |
| Width of packaging (single piece)  | 200 mm             |
| Depth of packaging (single piece)  | 240 mm             |
| Package weight (single piece)      | 0.036 kg           |