

ROLINE U/FTP DataCenter Patch Cord Cat.6A (Class EA), LSOH, slim, white, 2 m

Product No.	21.15.1702
Manufacturer	ROLINE
Manufacturer No.	21.15.1702
EAN (single piece)	7630049610699



Category 6a twisted-pair patch cable with shielded RJ-45 connectors on both sides. Particularly thin and flexible cable with individual pairs of wires in aluminium-laminated foil for use in confined spaces, such as in data centres.

- Durable thanks to moulded-on kink protection
- Suitable as patch cable in patch panels or as device connection cable and intended for use in the LAN
- Contact assignment: 1:1 according to EIA/TIA568, 8 cores
- Structure: 8 cores stranded wire, pairs shielded with alu-laminated foil

Technical specifications

Manufacturer	ROLINE
Product group	Twisted Pair Cable
Product type	FTP Patch Cord
Colour	white
Length	2 m
Shield type	FTP

Transfer quality	Cat6A / Class EA
------------------	------------------

Quantity of wires	8
-------------------	---

Conductor type	Wire
----------------	------

Crossed	no
---------	----

Slim cable	yes
------------	-----

Locking lever	yes
---------------	-----

Anti-kink sleeve	Moulded-on
------------------	------------

Colour (Spout)	white
----------------	-------

Cable LSOH	yes
------------	-----

Side 1 Connector Type	RJ-45
-----------------------	-------

Side 1 Connector Gender	Male
-------------------------	------

Side 2 Connector Type	RJ-45
-----------------------	-------

Side 2 Connector Gender	Male
-------------------------	------

Connector Type RJ45	Standard
---------------------	----------

Operating temperature min.	-10 °C
----------------------------	--------

Operating temperature max.	60 °C
----------------------------	-------

Weight	32.5 g
--------	--------

Height of packaging (single piece)	10 mm
------------------------------------	-------

Width of packaging (single piece)	100 mm
-----------------------------------	--------

Depth of packaging (single piece)	100 mm
-----------------------------------	--------

Package weight (single piece)	0.044 kg
-------------------------------	----------