## ROLINE U/FTP DataCenter Patch Cord Cat.6A (Class EA), LSOH, slim, grey, 1 m

**Product No.** 21.15.3303


Designed for Profe

**Manufacturer** ROLINE

Manufacturer No. 21.15.3303

**EAN (single piece)** 7630049622173













Category 6a twisted-pair patch cable with shielded RJ-45 connectors on both sides. Particularly thin and flexible cable with individual pairs of wires in aluminium-laminated foil for use in confined spaces, such as in data centres.

- Durable thanks to moulded-on kink protection
- Suitable as patch cable in patch panels or as device connection cable and intended for use in the LAN
- Contact assignment: 1:1 according to EIA/TIA568, 8 cores
- Structure: 8 cores stranded wire, pairs shielded with alu-laminated foil

| Technical specifications |                    |
|--------------------------|--------------------|
| Manufacturer             | ROLINE             |
| Product group            | Twisted Pair Cable |
| Product type             | FTP Patch Cord     |
| Colour                   | grey               |
| Length                   | 1 m                |
| Shield type              | FTP                |

| Transfer quality                   | Cat6A / Class EA |
|------------------------------------|------------------|
| Quantity of wires                  | 8                |
| Conductor type                     | Wire             |
| Crossed                            | no               |
| Slim cable                         | yes              |
| Locking lever                      | yes              |
| Anti-kink sleeve                   | Moulded-on       |
| Colour (Spout)                     | grey             |
| Cable LSOH                         | yes              |
| Side 1 Connector Type              | RJ-45            |
| Side 1 Connector<br>Gender         | Male             |
| Side 2 Connector Type              | RJ-45            |
| Side 2 Connector<br>Gender         | Male             |
| Connector Type RJ45                | Standard         |
| Operating temperature min.         | -10 °C           |
| Operating temperature max.         | 60 °C            |
| Weight                             | 19 g             |
| Height of packaging (single piece) | 20 mm            |
| Width of packaging (single piece)  | 50 mm            |
| Depth of packaging (single piece)  | 50 mm            |
| Package weight (single piece)      | 0.02 kg          |