
ROLINE U/FTP DataCenter Patch Cord Cat.6A (Class EA), LSOH, slim, red, 5 m

ne

| Product No. | 21.15.3317 | roli Designed for Pref |
|--------------------|---------------|---------------------------|
| Manufacturer | ROLINE | |
| Manufacturer No. | 21.15.3317 | |
| EAN (single piece) | 7630049622296 | |
| | | |



Category 6a twisted-pair patch cable with shielded RJ-45 connectors on both sides. Particularly thin and flexible cable with individual pairs of wires in aluminiumlaminated foil for use in confined spaces, such as in data centres.

- Durable thanks to moulded-on kink protection
- $\ensuremath{\cdot}$ Suitable as patch cable in patch panels or as device connection cable and intended for use in the LAN
- Contact assignment: 1:1 according to EIA/TIA568, 8 cores
- Structure: 8 cores stranded wire, pairs shielded with alu-laminated foil

| Technical specifications | | |
|--------------------------|--------------------|--|
| Manufacturer | ROLINE | |
| Product group | Twisted Pair Cable | |
| Product type | FTP Patch Cord | |
| Colour | red | |
| Length | 5 m | |
| Shield type | FTP | |

| Transfer quality | Cat6A / Class EA |
|---------------------------------------|------------------|
| Quantity of wires | 8 |
| Conductor type | Wire |
| Crossed | no |
| Slim cable | yes |
| Locking lever | yes |
| Anti-kink sleeve | Moulded-on |
| Colour (Spout) | red |
| Cable LSOH | yes |
| Side 1 Connector Type | RJ-45 |
| Side 1 Connector Gender | Male |
| Side 2 Connector Type | RJ-45 |
| Side 2 Connector Gender | Male |
| Connector Type RJ45 | Standard |
| Operating temperature min. | -10 °C |
| Operating temperature max. | 60 °C |
| Weight | 77.2 g |
| Height of packaging (single piece) | 30 mm |
| Width of packaging (single piece) | 100 mm |
| Depth of packaging (single piece) | 100 mm |
| Package weight (single piece) | 0.08 kg |