

# ROLINE 19-inch wall-mounted housing Pro 22 U, 600x600 WxD IP55 outdoor grey

|                           |               |
|---------------------------|---------------|
| <b>Product No.</b>        | 26.21.0092    |
| <b>Manufacturer</b>       | ROLINE        |
| <b>Manufacturer No.</b>   | 26.21.0092    |
| <b>EAN (single piece)</b> | 7630049600935 |



## 19 inch wall-mounted housing Pro 22 U 600x600 WxD IP55 outdoor grey

The outdoor network enclosures for wall mounting are developed in accordance with protection class IP55 and are specially designed for use in harsh environments, particularly outdoors. The wall-mounted enclosures offer a 3-point locking system with lockable swivelling handle and insulated PG cable glands. Integrated ventilation filter housings ensure ventilation and provide protection against water and dust in accordance with IP54. These enclosures are ideal for outdoor areas that are exposed to environmental influences such as rain, hail and splash water. The roof chassis is equipped with a filtered area for the installation of a fan module. Inside there is a pair (from 600 mm depth two pairs) of galvanised 19" profile rails, which can be read in both directions and are adjustable in depth. Each cabinet consists of a robust steel construction with a material thickness of up to 2.0 mm.

### Technical specifications

|                   |   |
|-------------------|---|
| Manufacturer      | ROLINE  |
| Product group     | 19"- / 10" technology   |
| Product type      | 19"-Outdoor wall housing  |
| Colour            | grey  |
| Scope of delivery | 19-inch wall-mounted housing Pro 22 U, earthing cable set, 2x spanners, installation set (screws, cage nuts, washers) |

|                                    |                     |
|------------------------------------|---------------------|
| Height units                       | 22 U                |
| Minimum rack depth supported       | 260 mm              |
| Maximum rack depth supported       | 535 mm              |
| delivery condition                 | fully assembled     |
| Material group                     | Steel               |
| Wall mountable                     | yes                 |
| Adjustable feet                    | no                  |
| Protection class (IP Code)         | IP55                |
| Soundproof                         | no                  |
| Front                              | Steel door          |
| Rack rails                         | no                  |
| Side panels included               | no                  |
| Removeable side panels             | no                  |
| Removable front door               | yes                 |
| Removable back door                | no                  |
| Ventilation                        | Passive             |
| RAL colour                         | RAL 7035 Light grey |
| Height                             | 1157 mm             |
| Width                              | 600 mm              |
| Depth                              | 600 mm              |
| Weight                             | 61 kg               |
| Height of packaging (single piece) | 1180 mm             |
| Width of packaging (single piece)  | 690 mm              |
| Depth of packaging (single piece)  | 630 mm              |
| Package weight (single piece)      | 64.1 kg             |