

ROLINE 19-inch Server Cabinet Basic 42 U, 800x1000 WxD perforated black

| | |
|---------------------------|---------------|
| Product No. | 26.21.0215 |
| Manufacturer | ROLINE |
| Manufacturer No. | 26.21.0215 |
| EAN (single piece) | 7630049602182 |



ROLINE 19 inch Server Cabinet Basic 42 U 800x1000 WxD perforated black

The network cabinets in the ROLINE Basic series were developed to enable simple and particularly cost-efficient network expansion. Strategically placed cable inlets ensure effortless installation depending on the application. The cable inlet is located in the base chassis, protected by a screwed cover plate and positioned in the rear centre area. For enclosures from 800 mm width, additional cable inlets with plastic covers are added on the left and right. These are also integrated in the roof (once for 600 mm enclosure width, three times for 800 mm enclosure width). The roof chassis also has a punched-out area for the installation of a fan module. Two pairs of galvanised 19" profile rails are installed inside, which can be read in both directions and can be adjusted in depth. They are also connected to additional depth struts in the enclosure. Each cabinet consists of a robust steel construction with a material thickness of up to 1.5 mm sheet steel.

The colouring is done using electrostatic powder coating in the standard colours grey (RAL 7035) and black (RAL 9005). Removable side and rear panels as well as a lockable and removable front door improve accessibility. It is possible to change the door hinge. Thanks to their demountable design, the cabinets can also be completely dismantled if required.

Technical specifications

| | |
|---------------|--------------------|
| Manufacturer | ROLINE |
| Product group | 19"/-10"-Cabinet |
| Product type | 19"-Server cabinet |

| | |
|------------------------------|---|
| Colour | black |
| Scope of delivery | 19-inch server enclosure Basic 42 U, earthing cable set, installation set (screws, cage nuts, washers), 2x spanners, instructions |
| Height units | 42 U |
| Minimum rack depth supported | 630 mm |
| Maximum rack depth supported | 950 mm |
| delivery condition | fully assembled |
| Material group | Steel |
| Server cabinet | yes |
| Wall mountable | no |
| Adjustable feet | yes |
| Maximum weight capacity | 600 kg |
| Protection class (IP Code) | IP20 |
| Soundproof | no |
| Front | Steel door with perforation |
| Rack rails | yes |
| Side panels included | yes |
| Removeable side panels | yes |
| Removable front door | yes |
| Removable back door | no |
| Ventilation | Passive |
| RAL colour | RAL 9005 Jet black |
| Height | 2010 mm |
| Width | 800 mm |
| Depth | 1000 mm |
| Weight | 113.8 kg |

| | |
|---------------------------------------|---------|
| Height of packaging (single piece) | 2150 mm |
|---------------------------------------|---------|

| | |
|--------------------------------------|--------|
| Width of packaging (single piece) | 880 mm |
|--------------------------------------|--------|

| | |
|--------------------------------------|---------|
| Depth of packaging (single piece) | 1080 mm |
|--------------------------------------|---------|

| | |
|----------------------------------|--------|
| Package weight (single piece) | 119 kg |
|----------------------------------|--------|