VALUE Cable USB 2.0, C-C, M/M, 100W, with Emark, black, 2 m

Product No. 11.99.8309

Manufacturer VALUE

Manufacturer No. 11.99.8309

EAN (single piece) 7630049624948







- High quality USB 2.0 cable with improved shielding
- With the reversible Type C connectors at both ends
- Gold-plated contacts for low wear at high plugging cycles
- Suitable for data transfer rates of up to 480 Mbit/s
- Supports USB Power Delivery to 20V / 5A

Technical specifications	
Manufacturer	VALUE
Product group	Cable
Product type	USB 2.0 Cable
Colour	black
Length	2 m
Transfer quality	USB 2.0 Hi-Speed 480 Mbit/s
Connection ports	USB Type C (USB-C) Male / USB Type C (USB-C) Male
Side 1 Connector Type	USB Type C (USB-C)
Side 1 Connector Gender	Male
Side 2 Connector Type	USB Type C (USB-C)

Side 2 Connector Gender Maximum data transfer rate Area of application Supported charging technology Power (max.) Cable shielding Hand locking screws Weight 75.4 g Height of packaging (single piece) Width of packaging (single piece) Depth of packaging (some served was as a single piece) Male A80 Mbit/s A80 Mbit/s External Area of application External Power Delivery 3.0 External Supported charging Fower Delivery 3.0 External 20 W Too W Too W Too Male 100 mm		
Area of application External Supported charging technology Power (max.) 100 W Cable shielding Screened Hand locking screws no Weight 75.4 g Height of packaging (single piece) Width of packaging (single piece) 100 mm		Male
Supported charging technology Power (max.) Cable shielding Hand locking screws Weight 75.4 g Height of packaging (single piece) Width of packaging (single piece)		480 Mbit/s
Power (max.) 100 W Cable shielding Screened Hand locking screws no Weight 75.4 g Height of packaging (single piece) Width of packaging (single piece)	Area of application	External
Cable shielding Screened Hand locking screws no Weight 75.4 g Height of packaging (single piece) Width of packaging (single piece) 100 mm (single piece)		Power Delivery 3.0
Hand locking screws no Weight 75.4 g Height of packaging (single piece) Width of packaging (single piece)	Power (max.)	100 W
Weight 75.4 g Height of packaging 20 mm (single piece) Width of packaging 100 mm (single piece)	Cable shielding	Screened
Height of packaging 20 mm (single piece) Width of packaging 100 mm (single piece)	Hand locking screws	no
(single piece) Width of packaging 100 mm (single piece)	Weight	75.4 g
(single piece)		20 mm
Depth of packaging 100 mm		100 mm
(single piece)		100 mm
Package weight (single 0.075 kg piece)		0.075 kg