


VALUE USB 3.2 Gen 1 Cable, A-C, M/M, white, 2 m

| | |
|---------------------------|---------------|
| Product No. | 11.99.9035 |
| Manufacturer | VALUE |
| Manufacturer No. | 11.99.9035 |
| EAN (single piece) | 7630049621220 |



- Improved data encoding for more efficient data transfer leading to higher through-put and improved I/O power efficiency
- Compatible with existing USB 3.0 / USB 3.2 Gen 1 software stacks and device protocols
- Works with both existing 5 Gbit/s USB 3.0 / USB 3.2 Gen 1 hubs and devices, as well as USB 2.0 products
- The USB type-C defines a new small reversible-plug connector for USB 3.0 / USB 3.2 Gen 1 devices
- The type-C plug can be used at both host and device side, replacing multiple type-B and type-A connectors and cables
- USB 3.1 high-speed cable in high quality with improved shielding
- Only suitable for USB standard power supply to 5V / 900mA!
- Type: A-C
- Colour: white

Note: According to the current specifications of USB.org we have adapted the technical data of our USB 3 products. The new designation for the already known USB specifications has been changed to USB 3.2 Gen 1 (formerly USB 3.0 / USB 3.1 Gen 1) and USB 3.2 Gen 2 (formerly USB 3.1 / USB 3.1 Gen 2).

Technical specifications

| | |
|---------------|---------------|
| Manufacturer | VALUE |
| Product group | Cable |
| Product type | USB 3.2 Cable |

| | |
|------------------------------------|--|
| Colour | white |
| Length | 2 m |
| Transfer quality | USB 3.2 Gen 1 SuperSpeed 5 Gbit/s (USB 3.1 Gen 1, USB 3.0) |
| Connection ports | USB 3 Type A Male / USB Type C (USB-C) Male |
| Side 1 Connector Type | USB 3 Type A |
| Side 1 Connector Gender | Male |
| Side 2 Connector Type | USB Type C (USB-C) |
| Side 2 Connector Gender | Male |
| Maximum data transfer rate | 5 Gbit/s |
| Area of application | External |
| Power (max.) | 4.5 W |
| Cable shielding | Screened |
| Hand locking screws | no |
| Weight | 69.4 g |
| Height of packaging (single piece) | 20 mm |
| Width of packaging (single piece) | 100 mm |
| Depth of packaging (single piece) | 100 mm |
| Package weight (single piece) | 0.088 kg |