

# VALUE Outdoor S/FTP Patch Cord Cat.6A/Class EA, Solid, TPE, LSOH, black, 50 m

<b>Product No.</b>	21.99.0722
<b>Manufacturer</b>	VALUE
<b>Manufacturer No.</b>	21.99.0722
<b>EAN (single piece)</b>	7630049627444



## Patch cord for outdoor use, e.g. for connecting an IP camera

Patch cords for networking connections between devices in combination with outdoor application (e.g. connection to outdoor surveillance cameras)

- Assembled double shielded (PIMF) twisted pair cable made of solid wire in category 6A with shielded RJ-45 connectors on both sides.
- Suitable for connecting external components (e.g. IP cameras), but also for PoE applications or as TP extension cable in multimedia applications
- UV - resistant
- Durable thanks to molded bend protection
- Contact assignment: 1:1 according to EIA/TIA568, 8 cores
- Construction: 8 cores solid wire. Pair shielding: aluminum-clad polyester foil. Overall shielding: copper braiding
- High quality gold plated contacts

REMARK: NOT suitable for underground installation / application

Important: Not suitable for underground installation. RJ-45 connectors must be protected from the influence of the weather.

## Technical specifications

Manufacturer	VALUE
Product group	Twisted Pair Cable
Product type	S/FTP Patchcord
Colour	black
Length	50 m
Shield type	PiMF
Transfer quality	Cat6A / Class EA
Quantity of wires	8
Conductor type	Solid wire
Crossed	no
Locking lever	yes
Anti-kink sleeve	Moulded-on
Cable LSOH	yes
Material (external cable mantle)	TPE
Side 1 Connector Type	RJ-45
Side 1 Connector Gender	Male
Side 2 Connector Type	RJ-45
Side 2 Connector Gender	Male
Connector Type RJ45	Standard
Operating temperature min.	-10 °C
Operating temperature max.	60 °C
Weight	1755 g
Height of packaging (single piece)	50 mm
Width of packaging (single piece)	240 mm

---

Depth of packaging (single piece)	240 mm
--------------------------------------	--------

Package weight (single piece)	1.5 kg
----------------------------------	--------