

# VALUE S/FTP Patch Cord Cat.6 (Class E), halogen-free, black, 2 m

<b>Product No.</b>	21.99.1245
<b>Manufacturer</b>	VALUE
<b>Manufacturer No.</b>	21.99.1245
<b>EAN (single piece)</b>	7611990113958



Prepared shielded Twisted Pair cable with RJ-45 connectors on both sides. Used as patch cable in wiring cabinet or as direct connection cable between devices. Flexible cable suitable for narrow bending. Contact settings 1:1, according to EIA/TIA 568, 8 wires. Construction: 8 wires stranded copper wire, braided shield. Impedance:100 Ohm. Cable jacketing: LSOH - Low Smoke Zero Halogen - cable emits limited smoke and no halogens when exposed to high sources of heat. For a structured cabling system we recommend to use the following components: ROLINE Cat.6 S/FTP Cable, Solid Wire, LSOH: 21.15.1889. VALUE Cat.6 Flush/Surface Mount Wall Jack, shielded, white: 25.99.8492/25.99.8392. VALUE Cat.6 19" Patch Panel, 24 Ports, shielded: 26.99.0353 (black), 26.99.0354 (grey). VALUE Cat.6 S/FTP Patch Cord, LSOH, grey, 5 m: 21.99.0705. Our in-house laboratory has tested this cable-plug combination, in a Channel of 100 meters, in compliance with Class E specifications.

## Technical specifications

Manufacturer	VALUE
Product group	Twisted Pair Cable
Product type	S/FTP Patchcord
Colour	black

Length	2 m
Shield type	SFTP
Transfer quality	Cat6 / Class E
Impedance	100 Ohm
Quantity of wires	8
Conductor type	Wire
Crossed	no
Assignment	1:1
Locking lever	yes
Anti-kink sleeve	Moulded-on
Colour (Spout)	black
Cable LSOH	yes
Side 1 Connector Type	RJ-45
Side 1 Connector Gender	Male
Side 2 Connector Type	RJ-45
Side 2 Connector Gender	Male
Connector Type RJ45	Standard
Weight	63.6 g
Height of packaging (single piece)	30 mm
Width of packaging (single piece)	130 mm
Depth of packaging (single piece)	150 mm
Package weight (single piece)	0.066 kg