

# VALUE S/FTP Patch Cord Cat.6 (Class E), halogen-free, blue, 3 m

|                           |               |
|---------------------------|---------------|
| <b>Product No.</b>        | 21.99.1254    |
| <b>Manufacturer</b>       | VALUE         |
| <b>Manufacturer No.</b>   | 21.99.1254    |
| <b>EAN (single piece)</b> | 7611990114016 |



Prepared shielded Twisted Pair cable with RJ-45 connectors on both sides. Used as patch cable in wiring cabinet or as direct connection cable between devices. Flexible cable suitable for narrow bending. Contact settings 1:1, according to EIA/TIA 568, 8 wires. Construction: 8 wires stranded copper wire, braided shield. Impedance:100 Ohm. Cable jacketing: LSOH - Low Smoke Zero Halogen - cable emits limited smoke and no halogens when exposed to high sources of heat. For a structured cabling system we recommend to use the following components: ROLINE Cat.6 S/FTP Cable, Solid Wire, LSOH: 21.15.1889. VALUE Cat.6 Flush/Surface Mount Wall Jack, shielded, white: 25.99.8492/25.99.8392. VALUE Cat.6 19" Patch Panel, 24 Ports, shielded: 26.99.0353 (black), 26.99.0354 (grey). VALUE Cat.6 S/FTP Patch Cord, LSOH, grey, 5 m: 21.99.0705. Our in-house laboratory has tested this cable-plug combination, in a Channel of 100 meters, in compliance with Class E specifications.

## Technical specifications

|               |                    |
|---------------|--------------------|
| Manufacturer  | VALUE              |
| Product group | Twisted Pair Cable |
| Product type  | S/FTP Patchcord    |
| Colour        | blue               |

|                                    |                |
|------------------------------------|----------------|
| Length                             | 3 m            |
| Shield type                        | SFTP           |
| Transfer quality                   | Cat6 / Class E |
| Impedance                          | 100 Ohm        |
| Quantity of wires                  | 8              |
| Conductor type                     | Wire           |
| Crossed                            | no             |
| Assignment                         | 1:1            |
| Locking lever                      | yes            |
| Anti-kink sleeve                   | Moulded-on     |
| Colour (Spout)                     | blue           |
| Cable LSOH                         | yes            |
| Side 1 Connector Type              | RJ-45          |
| Side 1 Connector Gender            | Male           |
| Side 2 Connector Type              | RJ-45          |
| Side 2 Connector Gender            | Male           |
| Connector Type RJ45                | Standard       |
| Weight                             | 90.5 g         |
| Height of packaging (single piece) | 30 mm          |
| Width of packaging (single piece)  | 140 mm         |
| Depth of packaging (single piece)  | 140 mm         |
| Package weight (single piece)      | 0.09 kg        |