

# VALUE S/FTP (PiMF) Patch Cord, Cat.6 (Class E), yellow, 0.5 m

**Product No.** 21.99.1322  
**Manufacturer** VALUE  
**Manufacturer No.** 21.99.1322  
**EAN (single piece)** 7611990177394



Patch cable for networking connections between devices. Prepared double shielded Twisted Pair cable with screened RJ-45 connectors on both ends. Durable due to moulded kink protection. Flexible cable, suitable for narrow bending. Plugs with gold plated contacts. Contact settings 1:1, in accordance with the EIA/TIA 568 standard. Construction: 4-pair stranded wire. Complete braid shielding. Pairs shielded with aluminium clad polyester foil.

For a structured cabling system we recommend to use the following components: ROLINE Cat.6 S/FTP Cable, Solid Wire, AWG23: 21.15.0890 (100 m), 21.15.0891 (300 m); VALUE Cat.6 Flush/Surface Mount Wall Jack, shielded, white: 25.99.8492/25.99.8392; VALUE Cat.6 19" Patch Panel, 24 Ports, shielded: 26.99.0353 (black), 26.99.0354 (grey); VALUE Cat.6 S/FTP Patch Cord, grey, 5 m: 21.99.0805. Our in-house laboratory has tested this cable-plug combination, in a Channel of 100 meters, in compliance with Class E specifications.

## Technical specifications

|               |                          |
|---------------|--------------------------|
| Manufacturer  | VALUE                    |
| Product group | Twisted Pair Cable       |
| Product type  | S / FTP patch cable PiMF |
| Colour        | yellow                   |

|                                    |                |
|------------------------------------|----------------|
| Length                             | 0.5 m          |
| Shield type                        | PiMF           |
| Transfer quality                   | Cat6 / Class E |
| Impedance                          | 100 Ohm        |
| Quantity of wires                  | 8              |
| Conductor type                     | Wire           |
| Crossed                            | no             |
| Assignment                         | 1:1            |
| Locking lever                      | no             |
| Anti-kink sleeve                   | Moulded-on     |
| Colour (Spout)                     | yellow         |
| Cable LSOH                         | no             |
| Side 1 Connector Type              | RJ-45          |
| Side 1 Connector Gender            | Male           |
| Side 2 Connector Type              | RJ-45          |
| Side 2 Connector Gender            | Male           |
| Connector Type RJ45                | Standard       |
| Operating temperature min.         | -20 °C         |
| Operating temperature max.         | 60 °C          |
| Weight                             | 21.6 g         |
| Height of packaging (single piece) | 10 mm          |
| Width of packaging (single piece)  | 85 mm          |
| Depth of packaging (single piece)  | 85 mm          |
| Package weight (single piece)      | 0.032 kg       |