VALUE UTP Patch Cord Cat.6A (Class EA), blue, 0.3 m


Product No. 21.99.1454

Manufacturer VALUE

Manufacturer No. 21.99.1454

EAN (single piece) 7630049612334











The affordable solution for Category 6A cabling for data rates up to 10Gbit / s. Twisted pair connection cable with RJ-45 connectors plugged in on both sides

- Suitable as a patch cord in patch panels or as a device connection cable
- Durable with molded kink protection
- Contact assignment 1: 1 according to EIA / TIA 568, 8 cores
- · Construction: 8 cores wire
- Impedance: 100 ohms

For a structured shielded Cat.6a cabling system we recommend to use the following components:

VALUE Cat.6a UTP Cable, Solid Wire, 300 m: 21.99.1681

Flush Mount Wall Jack for Keystones: 25.16.8579

Surface Wall Mount Frame: 25.16.8484

VALUE Cat.6a Keystone, RJ-45, shielded: 26.99.0366 19" Keystone Patch Panel: 26.11.0358 / 26.11.0359 VALUE Cat.6a S/FTP Patch Cord, 5 m: 21.99.0875

Technical specifications

Manufacturer VALUE

| Product group | Twisted Pair Cable |
|------------------------------------|--------------------|
| Product type | UTP Patch Cables |
| Colour | blue |
| Length | 0.3 m |
| Shield type | UTP |
| Transfer quality | Cat6A / Class EA |
| Quantity of wires | 8 |
| Conductor type | Wire |
| Crossed | no |
| Assignment | 1:1 |
| Locking lever | yes |
| Anti-kink sleeve | Moulded-on |
| Colour (Spout) | blue |
| Cable LSOH | no |
| Side 1 Connector Type | RJ-45 |
| Side 1 Connector Gender | Male |
| Side 2 Connector Type | RJ-45 |
| Side 2 Connector Gender | Male |
| Connector Type RJ45 | Standard |
| Operating temperature min. | -20 °C |
| Operating temperature max. | 60 °C |
| Weight | 16 g |
| Height of packaging (single piece) | 20 mm |
| Width of packaging (single piece) | 130 mm |
| Depth of packaging (single piece) | 140 mm |
| | |

Package weight (single 0.028 kg piece)