


VALUE UTP Patch Cord, Cat.6 (Class E), white, 1 m

Product No.	21.99.1536
Manufacturer	VALUE
Manufacturer No.	21.99.1536
EAN (single piece)	7611990193752



Patch cable for networking connections between devices. Prepared unshielded Twisted Pair cable with RJ-45 connectors on both ends. Durable due to moulded kink protection. Flexible cable, suitable for narrow bending. Plugs with gold plated contacts. Contact settings 1:1, in accordance with the EIA/TIA 568 standard. Construction: 4-pair stranded wire.

For a structured cabling system we recommend to use the following components: VALUE Cat.6 UTP Cable, Solid Wire, AWG24, 300 m: 21.99.0995. VALUE Cat.6 Flush/Surface Mount Wall Jack, unshielded, white: 25.99.8494/25.99.8394; VALUE Cat.6 19" Patch Panel, 24 Ports, unshielded: 26.99.0351 (black), 26.99.0352 (grey); VALUE Cat.6 UTP Patch Cord, grey, 5 m: 21.99.0905. Our in-house laboratory has tested this cable-plug combination, in a Channel of 100 meters, in compliance with Class E specifications.

Technical specifications

Manufacturer	VALUE
Product group	Twisted Pair Cable
Product type	UTP Patch Cables
Colour	white
Length	1 m
Shield type	UTP

Transfer quality	Cat6 / Class E
------------------	----------------

Impedance	100 Ohm
-----------	---------

Quantity of wires	8
-------------------	---

Conductor type	Wire
----------------	------

Crossed	no
---------	----

Locking lever	no
---------------	----

Anti-kink sleeve	Moulded-on
------------------	------------

Colour (Spout)	white
----------------	-------

Cable LSOH	no
------------	----

Side 1 Connector Type	RJ-45
-----------------------	-------

Side 1 Connector Gender	Male
-------------------------	------

Side 2 Connector Type	RJ-45
-----------------------	-------

Side 2 Connector Gender	Male
-------------------------	------

Connector Type RJ45	Standard
---------------------	----------

Weight	33.4 g
--------	--------

Height of packaging (single piece)	15 mm
------------------------------------	-------

Width of packaging (single piece)	125 mm
-----------------------------------	--------

Depth of packaging (single piece)	140 mm
-----------------------------------	--------

Package weight (single piece)	0.04 kg
-------------------------------	---------