

VALUE FO Jumper Cable 50/125µm OM4, LC/LC, Low-Loss-Connector, violet, 2 m

| | |
|---------------------------|---------------|
| Product No. | 21.99.8832 |
| Manufacturer | VALUE |
| Manufacturer No. | 21.99.8832 |
| EAN (single piece) | 7630049616875 |



VALUE F.O. Patchcable in OM4-Quality for a high performance connection.

- Security for the future! The OM4 fiber and connector quality with very low insertion ensure an excellent quality at very high bandwidths.
- It supports 10 Gb/s Ethernet, Fibre Channel, and OIF applications to 550 meters, extends the system cost benefits to ultra long building backbones and medium length campus backbones.
- The cable assembled with "low-loss" connectors achieve very good values for insertion loss and reflection. In comparison:
 - Typical attenuation of a standard LC connector: 0.5 dB
 - Typical attenuation of a low-loss LC connector: 0.15 dB
- Modal Bandwidth: 4700 MHz-km (this bandwidth is based on application-specific implementation of the EMBC requirements)
- Duplex cables with fiber type Multi-mode 50/125µm, OM4

Technical specifications

| | |
|---------------|-------------------------------|
| Manufacturer | VALUE |
| Product group | Fibre optic cable |
| Product type | Fibre Optic Jumper Cables OM4 |

| | |
|---------------------------------------|-------------------|
| Colour | violet |
| Length | 2 m |
| Quantity of fibre | 2 |
| Conductor composition | Compact conductor |
| Cable type | Duplex Cable |
| External cable | no |
| Fibre section | 50/125µm OM4 |
| Connection ports | LC / LC |
| Side 1 Connector Type | LC |
| side 1 connector ferrules | low loss |
| Side 2 Connector Type | LC |
| side 2 connector ferrules | low loss |
| Aramid strain relief | yes |
| External cable diameter | 2 x 4 mm |
| Mantle of external cable | LS0H |
| Cable LSOH | yes |
| Weight | 20.2 g |
| Height of packaging (single piece) | 10 mm |
| Width of packaging (single piece) | 80 mm |
| Depth of packaging (single piece) | 80 mm |
| Package weight (single piece) | 0.02 kg |