

ROLINE GREEN U/FTP DataCenter Patch Cord Cat.6A (Class EA), LSOH, slim, white, 0.3 m

| | |
|---------------------------|---------------|
| Product No. | 21.44.1699 |
| Manufacturer | ROLINE GREEN |
| Manufacturer No. | 21.44.1699 |
| EAN (single piece) | 7630049624214 |



Category 6a twisted-pair patch cable with shielded RJ-45 connectors on both sides. Particularly thin and flexible cable with individual pairs of wires in aluminium-laminated foil for use in confined spaces, such as in data centres.

- Durable thanks to moulded-on kink protection
- Suitable as patch cable in patch panels or as device connection cable and intended for use in the LAN
- Contact assignment: 1:1 according to EIA/TIA568, 8 cores
- Structure: 8 cores stranded wire, pairs shielded with alu-laminated foil

ROLINE GREEN products are marked only with a paper tag and build with halogen-free TPE material, without plastic bags and without plastic cable straps for use in eco-friendly environments.

Technical specifications

| | |
|---------------|--------------------|
| Manufacturer | ROLINE GREEN |
| Product group | Twisted Pair Cable |
| Product type | FTP Patch Cord |

| | |
|------------------------------------|---|
| Colour | white |
| Length | 0.3 m |
| Scope of delivery | Cable without plastic bag, only marked with a paper label |
| Shield type | FTP |
| Transfer quality | Cat6A / Class EA |
| Quantity of wires | 8 |
| Conductor type | Wire |
| Crossed | no |
| Slim cable | yes |
| Locking lever | yes |
| Anti-kink sleeve | Moulded-on |
| Colour (Spout) | white |
| Cable LSOH | yes |
| Material (external cable mantle) | LSOH-TPE |
| Side 1 Connector Type | RJ-45 |
| Side 1 Connector Gender | Male |
| Side 2 Connector Type | RJ-45 |
| Side 2 Connector Gender | Male |
| Connector Type RJ45 | Standard |
| Operating temperature min. | -10 °C |
| Operating temperature max. | 60 °C |
| Weight | 10.9 g |
| Height of packaging (single piece) | 20 mm |
| Width of packaging (single piece) | 50 mm |

| | |
|--------------------------------------|-------|
| Depth of packaging (single piece) | 50 mm |
|--------------------------------------|-------|

| | |
|----------------------------------|---------|
| Package weight (single piece) | 0.01 kg |
|----------------------------------|---------|