## ROLINE RM U/FTP DataCenter Patch Cord Cat.6A (Class EA), slim, yellow, 3 m

**Product No.** 21.45.3326

21.45.3326

ROLINE RECYCLED MATERIAL


Manufacturer No. 21.45.3326

**EAN (single piece)** 7630049630055



Manufacturer











Category 6a twisted-pair patch cable with shielded RJ-45 connectors on both sides. Particularly thin and flexible cable from our ROLINE Recycled Material product line with individual pairs of wires in aluminium-laminated foil for use in confined spaces, such as in data centres.

- Durable thanks to moulded-on kink protection
- Suitable as patch cable in patch panels or as device connection cable and intended for use in the LAN
- Contact assignment: 1:1 according to EIA/TIA568, 8 cores
- Structure: 8 cores stranded wire, pairs shielded with alu-laminated foil

## ROLINE RECYCLED MATERIAL products consist of more than 50% recycled materials. The packaging is even made from 100% recycled material.

Technical specifications		
Manufacturer	ROLINE RECYCLED MATERIAL	
Product group	Twisted Pair Cable	
Product type	FTP Patch Cord	

Length 3 m Shield type FTP Transfer quality Cat6A / Class EA Quantity of wires 8 Conductor type Wire Crossed no Slim cable yes Locking lever yes Anti-kink sleeve Moulded-on Side 1 Connector Type RJ-45 Side 1 Connector Male Gender Side 2 Connector Wale Gender Connector Type RJ-45 Side 2 Connector Type RJ-5 Side 2 Connector Type RJ-5 Side 2 Connector Type RJ-6 Side 3 Connector Type RJ-6 Side 4 Connector Type RJ-7 Side 5 Connector Type RJ-8 Side 6 Connector Type RJ-8 Side 7 Connector Type RJ-8 Side 9 Connector Type RJ-9 Storage temperature min. Operating temperature min. Storage t	Colour	yellow
Shield type FTP Transfer quality Cat6A / Class EA  Quantity of wires 8  Conductor type Wire Crossed no Slim cable yes Locking lever yes Anti-kink sleeve Moulded-on Side 1 Connector Type RJ-45 Side 1 Connector Type RJ-45 Side 2 Connector Type RJ-45 Side 2 Connector Type RJ-45 Side 2 Connector Type RJ-5 Side 3 Connector Type RJ-5 Side 2 Connector Type RJ-5 Side 3 Connector Type RJ-5 Side 3 Connector Type RJ-5 Side 4 Connector Type RJ-5 Side 5 Connector Type RJ-5 Side 6 Connector Type RJ-5 Side 7 Connector Type RJ-5 Side 9 Connector Type RJ-5 Side 1 Connector Type RJ-5 Side 1 Connector Type RJ-5 Side 2 Connector RJ-4 Side 2 Connector RJ-4 Side 3 Connector RJ-4 Side 3 Connector RJ-4 Side 4 Connector RJ-4 Side 3 Connector RJ-4 Side 4 Connector RJ-4 Side 4 Connector RJ-4 Side 5 Connector RJ-4 Side 6 Connector RJ-4 Side 7 Connector RJ-4 S		
Transfer quality Cat6A / Class EA  Quantity of wires 8  Conductor type Wire  Crossed no  Slim cable yes  Locking lever yes  Anti-kink sleeve Moulded-on  Side 1 Connector Type RJ-45  Side 2 Connector Wale  Gender Side 2 Connector Wale  Gender Connector Type RJ-45  Side 2 Connector Type RJ-45  Side 2 Connector Type RJ-5  Side 2 Connector Type RJ-6  Side 2 Connector Wale  Gender Connector Type RJ-5  Side 2 Connector Wale  Gender		
Quantity of wires     8       Conductor type     Wire       Crossed     no       Slim cable     yes       Locking lever     yes       Anti-kink sleeve     Moulded-on       Side 1 Connector Type     RJ-45       Side 2 Connector Gender     Male       Side 2 Connector Type     RJ-45       Side 2 Connector Gender     Male       Connector Type RJ45     Standard       Operating temperature min.     -20 °C       Storage temperature min.     -20 °C       Storage temperature max.     80 °C       Weight     45.9 g       Height of packaging (single piece)     20 mm       Width of packaging (single piece)     50 mm       Depth of packaging     50 mm	Shield type	FTP
Conductor type Wire Crossed no Slim cable yes Locking lever yes Anti-kink sleeve Moulded-on Side 1 Connector Type RJ-45 Side 1 Connector Gender Side 2 Connector Type RJ-45 Side 2 Connector Type RJ-45 Side 2 Connector Gender Connector Type RJ45 Standard Operating temperature min. Operating temperature min. Storage temperature min. Storage temperature max. Weight 45.9 g Height of packaging (single piece) Depth of packaging (single piece)  Width of packaging (single piece)  Depth of packaging Somm	Transfer quality	Cat6A / Class EA
Crossed no Slim cable yes Locking lever yes Anti-kink sleeve Moulded-on Side 1 Connector Type RJ-45 Side 1 Connector Gender Side 2 Connector Wale Gender Side 2 Connector Type RJ-45 Side 2 Connector RJ-45 Side 2 Co	Quantity of wires	8
Slim cable yes Locking lever yes Anti-kink sleeve Moulded-on Side 1 Connector Type RJ-45 Side 1 Connector Gender Side 2 Connector Type RJ-45 Side 2 Connector Type RJ-45 Side 2 Connector Male Gender Connector Type RJ-5 Standard Operating temperature min. Operating temperature max. Storage temperature -20 °C min. Storage temperature max. Storage temperature max. Weight 45.9 g Height of packaging (single piece) Depth of packaging So mm	Conductor type	Wire
Locking lever yes Anti-kink sleeve Moulded-on Side 1 Connector Type RJ-45 Side 1 Connector Male Gender Side 2 Connector Type RJ-45 Side 2 Connector Gender Connector Type RJ45 Standard Operating temperature min. Operating temperature max. Storage temperature min. Storage temperature max. Weight 45.9 g Height of packaging (single piece) Depth of packaging 50 mm	Crossed	no
Anti-kink sleeve Moulded-on Side 1 Connector Type RJ-45 Side 1 Connector Gender Side 2 Connector Wale Gender Connector Type RJ-45 Side 2 Connector Gender Connector Type RJ45 Standard Operating temperature min. Operating temperature min. Storage temperature min. Storage temperature max. Weight 45.9 g Height of packaging (single piece) Depth of packaging 50 mm	Slim cable	yes
Side 1 Connector Type RJ-45  Side 1 Connector Male Gender  Side 2 Connector Type RJ-45  Side 2 Connector Gender  Connector Type RJ45  Standard  Operating temperature min.  Operating temperature min.  Storage temperature min.	Locking lever	yes
Side 1 Connector Gender  Side 2 Connector Type RJ-45  Side 2 Connector Gender  Connector Type RJ45 Standard  Operating temperature min.  Operating temperature max.  Storage temperature min.  Storage temperature min.  Storage temperature min.  Weight 45.9 g  Height of packaging (single piece)  Width of packaging (single piece)  Depth of packaging 50 mm	Anti-kink sleeve	Moulded-on
Gender  Side 2 Connector Type RJ-45  Side 2 Connector Male  Connector Type RJ45 Standard  Operating temperature min.  Operating temperature max.  Storage temperature min.  Storage temperature max.  Storage temperature min.  St	Side 1 Connector Type	RJ-45
Side 2 Connector Gender  Connector Type RJ45 Standard  Operating temperature min.  Operating temperature max.  Storage temperature min.  Storage temperature max.  Storage temperature max.  Weight 45.9 g  Height of packaging (single piece)  Width of packaging (single piece)  Depth of packaging 50 mm		Male
Gender  Connector Type RJ45 Standard  Operating temperature rmin.  Operating temperature rmax.  Storage temperature rmin.  Storage temperature rmin.  Storage temperature rmax.  Weight 45.9 g  Height of packaging (single piece)  Width of packaging (single piece)  Depth of packaging 50 mm	Side 2 Connector Type	RJ-45
Operating temperature min.  Operating temperature 75 °C max.  Storage temperature -20 °C min.  Storage temperature 80 °C max.  Weight 45.9 g  Height of packaging (single piece)  Width of packaging (single piece)  Depth of packaging 50 mm		Male
min.  Operating temperature 75 °C max.  Storage temperature -20 °C min.  Storage temperature 80 °C max.  Weight 45.9 g  Height of packaging (single piece)  Width of packaging (single piece)  Depth of packaging 50 mm	Connector Type RJ45	Standard
max.  Storage temperature rinn.  Storage temperature rinn.  Storage temperature rinn.  Weight 45.9 g  Height of packaging (single piece)  Width of packaging (single piece)  Depth of packaging 50 mm		-20 °C
min.  Storage temperature max.  Weight 45.9 g  Height of packaging (single piece)  Width of packaging (single piece)  Depth of packaging 50 mm		75 °C
max.  Weight 45.9 g  Height of packaging (single piece)  Width of packaging (single piece)  Depth of packaging 50 mm		-20 °C
Height of packaging (single piece)  Width of packaging (single piece)  Depth of packaging 50 mm  50 mm		80 °C
(single piece)  Width of packaging 50 mm (single piece)  Depth of packaging 50 mm	Weight	45.9 g
(single piece)  Depth of packaging 50 mm		20 mm
		50 mm
		50 mm

Package weight (single 0.05 kg piece)